

NEAT OIL



SUPRACO 1315

DESCRIPTION

SUPRACO 1315 is a high-performance, biodegradable neat oil made with vegetable oils, which contains specific additives to reduce wear. With high lubricating and wear reducing power, **SUPRACO 1315** has been specially developed for machining by the removal of chippings from all metals, by means of micro-spraying.

ADVANTAGES

- High lubrication and cooling capacities
- Sprayable
- Enables the operator to monitor machining operations
- Multi-purpose; it can be used on all machines, even for applications with stringent requirements
- Low consumption
- Fully compatible with the materials used in the machines
- Optimum levels of safety in the workshop: inert towards operators and machine tools
- Protects parts from corrosion, does not mark alloys (aluminium, copper metals)

HEALTH AND SAFETY

- Free from organo-chlorinated additives
- Good dermatological behaviour and easy to use

APPLICATIONS

Machining Processes: Sawing, drilling, milling, tapping, reaming, broaching, bending, or punching ferrous and non-ferrous metals, including those with poor machinability.

MOTUL - 119, Bd Félix Faure BP 94 - 93303 AUBERVILLIERS CEDEX
Tél : +33 1 48 11 70 30 Fax : +33 1 48 11 70 38
www.motul.com

Version: 2.1
Date de création : 31-01-2013
Modification: 08/2014

NEAT OIL



SUPRACO 1315

TECHNICAL CHARACTERISTICS

Characteristics	Methods	units	SUPRACO 1315
Aspect			Transparent
Colour			Clear
Density at 15°C	ISO 12.185	kg/l	0.918
Viscosity at 40°C	ISO 3104	mm ² /s	Iso VG 15
Copper stripe corrosion	NTF M 07105		1a
Storage			Dry, frost-free space
Flash point	ASTM D 32	°C	214
Biodegradability	CEC L33T82		>60%

RECOMMENDATIONS

The MotulTech cutting oils SUPRACO range, are produced from highly refined base oils, and high quality additives. The usage of products from mineral oil requires care and caution when handling. All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance.

The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions.

To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com

MOTUL - 119, Bd Félix Faure BP 94 - 93303 AUBERVILLIERS CEDEX

Tél : +33 1 48 11 70 30 Fax : +33 1 48 11 70 38

www.motul.com

Version: 2.1


Date de création : 31-01-2013

Modification: 08/2014

2/3

**Technology for
industry**

NEAT OIL



SUPRACO 1315

MOTUL - 119, Bd Félix Faure BP 94 - 93303 AUBERVILLIERS CEDEX
Tél : +33 1 48 11 70 30 Fax : +33 1 48 11 70 38
www.motul.com

Version: 2.1
Date de création : 31-01-2013
Modification: 08/2014